



- MATERIAL AND FINISH
SHELL: DIE CAST ALUM. ALLOY PER FED SPEC QQ-A-591
FINISH: ELECTROLESS NICKEL PLATED PER MIL-C-26074, CLASS 1
INSULATOR HARD: EPOXY PER MIL-M-24325; SOFT: SILICONE RUBBER
GROMMET PROTECTORS: ALUM. ALLOY, FINISH: BLUE EPOXY
POLARIZING KEYING INSERTS & SCREWS: STAINLESS STEEL
FEMALE JACKSCREW: STAINLESS STEEL
SCREWS & WASHERS: STEEL, FINISH: CAD. PLATED PER QQ-P-416
DUST CAPS: CONDUCTIVE BLACK THERMOPLASTIC

- CONTACTS SHOWN IN POSITION FOR ILLUSTRATION ONLY, ARE INCLUDED IN A CONTAINER WITHIN CONNECTOR PACKAGE FOR SHIPMENT, EXCEPT P/N'S 1-207595-2 THRU 2-207595-1
- CONNECTOR MEETS AMP PRODUCT SPEC 108-10, 019
- COAX CONTACTS & SEALING BOOTS MUST BE ORDERED SEPARATELY

- ALL METRIC DIMENSIONS ARE SHOWN IN PARENTHESIS
- FOR MATING CONNECTOR SEE 207596
- CONNECTORS ORDERED LESS CONTACTS WILL BE MARKED WITH SAME P/N AS CONNECTORS ORDERED WITH CONTACTS

	INSERT ARRANGEMENT			
	26	32C2	67	106
"A" MAX	1.525 [38.74]	1.700 [43.18]	1.525 [38.74]	1.279 [32.49]

PART NO.	ARRANGEMENT		PART NO. ⁸ LESS CONTACTS
	MODULE A	MODULE B	
207595-1	106P	67S	1-207595-2
207595-2	106P	26S	1-207595-3
207595-3	106P	106P	1-207595-4
207595-4	106P	106S	1-207595-5
207595-5	106S	106S	1-207595-6
207595-6	106S	26P	1-207595-7
207595-7	106S	67P	1-207595-8
207595-8	67S	67S	1-207595-9
207595-9	106S	32C2P	2-207595-0
1-207595-0	106P	32C2S	2-207595-1
1-207595-1	NO INSERT	NO INSERT	-

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES ⁶	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN C.C.THOMAS 21MAR02	TE Connectivity
0 PLC ± -	1 PLC ± -	3-25-02	J.MARKEY
2 PLC ± -	3 PLC ± -	J.MARKEY 3-25-02	NAME
4 PLC ± -	ANGLES ± -	PRODUCT SPEC	RECEPTACLE CONNECTOR INSTALLATION (WITH CENTER FEMALE JACKSCREW)
MATERIAL	FINISH	APPLICATION SPEC	SIZE CASE CODE DRAWING NO
		WEIGHT	A1 00779 C=207595
		CUSTOMER DRAWING	SCALE 2:1 SHEET 1 OF 1 REV R