


REV. A  
DCO 144519

COIL: @ 25°C  
 RESISTANCE 720 OHMS ±10%  
 NOMINAL VOLTAGE 26.5 VDC  
 MUST OPERATE 13.5 VDC  
 MUST RELEASE 8.1 VDC MAX., 1.5 VDC MIN

ENVIRONMENT:  
 VIBRATION 10 Hz TO 3000 Hz @ 30 g's  
 SHOCK 75 g's 6 MS. DURATION  
 TEMPERATURE -65 °C TO +125 °C  
 NOTES: OPERATE 4 MS MAX  
RELEASE 4 MS MAX  
CONTACT STABILIZATION 2.5 MS MAX

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO  
2 AMPS 28 VDC RESISTIVE  
100,000 OPERATIONS

DR. B.D. 11SEP2008

CK. *ms 2/11/08*

**Tyco Electronics** ©COPYRIGHT 2005  
 TYCO ELECTRONICS CORPORATION  
 ALL INTERNATIONAL RIGHTS RESERVED

CUST. QPL  
 CUST. NO. M39016/14-008M REV. \_\_\_\_\_

TE NUMBER  
1-1617076-9

CII PART NUMBER  
3SBH1165A2