

Specification Sheet

Part Number: TAG69L-789

HellermannTyton Laser Tag Label, 2.0" x .275", 140 Per Sheet, PET, White, 1000/pkg

Article Number	594-69789
Type	TAG69L
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•Laser printable white polyester has a smooth surface, allowing for the highest resolution and print contrast.•The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.•Lasertags are not affected by the high heat required in a laser printer.
Quantity Per	pack
Product Description	HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 789 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

Short Description

Laser Tag Label, 2.0" x .275", 140 Per Sheet, PET, White, 1000/pkg

Global Part Name

TAG69L-789-WH

Length L (Imperial)

0.275

Length L (Metric)

6.98

Width W (Imperial)

2.0

Width W (Metric)

50.8

Thickness T (Metric)

64.0

Height H (Imperial)

0.275

Height H (Metric)

6.98

Material

Type 789, Polyester (PET)

Material Shortcut

789

Adhesive

Acrylic

Halogen free

No

Adhesive Operating Temperature

-40°F to +302°F (-40°C to +150°C)

Operating Temperature (Metric)

-40°F to +300°F (-40°C to +149°C)

Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3919905060
Labels per Column	35
Labels per Row	4
Weight (Metric)	0.521
Weight (Imperial)	1.14